Series 7

FULL SYNTHETIC COMPRESSOR FLUID



Series 7 compressor lubricants are formulated from several synthetic base stocks (PAO, Ester and Group III) and a synergistic blend of additives designed to provide excellent performance in rotary screw compressors. The Series 7 lubricants offer outstanding performance at a reduced cost versus most PAO and PAO blends.

The new Series 7 formulation provides better viscosity stability over a wide range of temperatures.

Application: Rotary Screw, Rotary Vane and Reciprocating Compressors.

Product life: 8.000 work hours

Product features & benefits

Outstanding Oxidation Stability High Viscosity Index High Flash & Auto-Ignition Points Low Volatility Extremely High Film Strength Excellent Coolant Properties Long Fluid Life Cycle

Energy Savings Carbon & Varnish Control Reduced Maintenance Cost Reduced Downtime Excellent Materials Compatibility Reduced Lubricant Consumption Excellent Rust & Corrosion Control

Product		KOA467C
Grado ISO		46
Viscosity Index		174
cSt @	100°F / 40°C	47,3
cSt @	212°F / 100°C	7,9
Flash Point	°F / °C	464 / 240
Pour Point	°F / °C	-17 / -27
Copper Corrosion, 24 Hr		1 a
Demulsibility, 30 Min @ 130 °F		Excellent



PNEUMA... MOVING AIR













