## **Series 7**

## **FULL SYNTHETIC COMPRESSOR FLUID**



Series 7 compressor lubricants are formulated from several synthetic base stocks (PAO, Ester and Group III) and a synergistic blend of additives designed to provide excellent performance in rotary screw compressors. The Series 7 lubricants offer outstanding performance at a reduced cost versus most PAO and PAO blends.

The new Series 7 formulation provides better viscosity stability over a wide range of temperatures.

**Application:** Rotary Screw, Rotary Vane and Reciprocating Compressors.

**Product life:** 8.000 work hours

## **Product features & benefits**

Outstanding Oxidation Stability
High Viscosity Index
High Flash & Auto-Ignition Points
Low Volatility
Extremely High Film Strength
Excellent Coolant Properties
Long Fluid Life Cycle

Energy Savings

Carbon & Varnish Control

Reduced Maintenance Cost

Reduced Downtime

Excellent Materials Compatibility

Reduced Lubricant Consumption

Excellent Rust & Corrosion Control

Product		KOA467C
Grado ISO		46
Viscosity Index		174
cSt @	100°F / 40°C	47,3
cSt @	212°F / 100°C	7,9
Flash Point	°F / °C	464 / 240
Pour Point	°F / °C	-17 / -27
Copper Corrosion, 24 Hr		<b>1</b> a
Demulsibility, 30 Min @ 130 °F		Excellent

